

NEW HHD9 8x6 11 ton front axle

GVW 62 ton @ 70km/h, 65 ton @ 40 km/h (according to I0/I0/20 standard)




Width 2,9 m

OPT according to Pricelist 2-2019

Possibility of CE Certification in combination with:

- Euro VI version
- OPT455
- Specific dump body and equipment including Rops Fops protection

AVAILABLE

Main technical data	HHD9 86.48	HHD9 86.48	HHD9 86.50
EMISSION	EURO III	EURO V	EURO VI
DRIVE	LHD	LHD (STD) – RHD (OPT)	LHD
CAB	AD – DAY		
ENGINES	C13 – 480 HP 2200 Nm	C13 – 480 HP 2200 Nm	C13 – 500 HP 2300 Nm
GEARBOXES	ZF AS2631 TO + INT ALLISON HD4700 + RET. 		
TRANSFER BOX	STEYR VG2700		
DRIVEN FRONT 1° AXLE	MERITOR 11 TON		
2° STEERING AXLE	MERITOR 11 TON		
REAR AXLES	MERITOR HUB REDUCTION 20 + 20 TON (WIDE VERSION)		
REAR AXLE RATIO	6,18 - 7,21		
FRONT SUSPENSION	PARABOLIC SPRING		
REAR SUSPENSION	PARABOLIC SPRING		
FRONT BRAKES	DISK (DOUBLE CALIPER)		
REAR BRAKES	DRUM (CAM)		
TIRES	14.00R20 (STD) - 325 / 95 R24 (OPT)		
CHASSIS FRAME	PARALLEL (820 WIDTH x 320 x 90 x 10+6 mm) - REINFORCED		
WHEELBASES (mm)	4750 / 5000		